

SAVING LIVES REQUIRES SPEED, STRENGTH, SMARTS AND FLEXIBILITY.

Now with removable spreader tips and optional door-opener tips, the SC 258 E3 Combi gets the job done quick. Its smart technology gives you all the power needed to save the day, above and below water.

TECHNICAL SPECIFICATIONS

- Length: 31.2 in / 792 mm
- Width: 8.27 in / 210 mm
- Height: 9.96 in / 253 mm
- Weight: 31.4 lbs / 14.1 kg
- Spreading Distance: 12.6 in / 321 mm
- Max Spreading Force: 157,000 lbs / 700 kN
- Max Pulling Force: 7,640 lbs / 34k kN
- NFPA HSF: 6,500 lbs / 29 kN
- NFPA LSF: 5,400 lbs / 24 kN
- NFPA HPF: 8,320 lbs / 37 kN
- NFPA LPF: 6,300 lbs / 28 kN
- NFPA Cutter Rating: A6/B6/C6/D7/E7/F4
- Cutter Opening: 9.2 in / 233 mm
- NFPA 1936 2020 Compliant: Yes
- IP Rating: IP58

ACCESSORIES

(See the end of the catalog for a full accessory listing.)

Rescue Batteries

9Ah EWXT/E3 Rescue Battery – 90-53-15 9Ah E3 Saltwater Battery - 90-53-18

Chain Set and Adapter

Part #: 541C068

Door-Opener Tips

Part #: 81-67-23



- Field-removable spreader tips
- Optional field-removable door-opener tips
- The perfect tool for police, military and first responder teams
- Smaller, lighter design enables easier and faster handling
- Watertight design makes it durable in fresh and salt water
- Smart dashboard displays live visual tool feedback
- Roll warnings, power levels and battery charge status are readily visible
- Dashboard reveals when a saltwater-capable battery has been installed
- New turbo function allows for a faster rescue
- Each package comes with two batteries and one charger

E3 CONNECT EXCLUSIVE

- The tool automatically receives and stores data and transfers it via Wi-Fi to a secure cloud
- Errors are detected early, and maintenance can be requested within Captium™
- Tool use is automatically documented with E3 CONNECT





